

轻商生产技术室
2026 04 16

3

4

6

6

13

13

14

1.1

1.2

GB/T 13564-2022

GB/T 43499-2024

GB/T 33191-2016

GB/T 13563-2007

GB/T 17993-2024

JT/T 478-2020

GA/T 708-2019

GA/T 134-2021

GB/T 26765-2021

GB/T 13423-2024

GA 329-2021

[1996] 090

[1998] 082

1.10

2.1

2-1

1

2 F &

3

đ

4

43

@+ēpR9 ã`ĐpF XpR9 iq- !

6		win11/64 2.3 33 31 3.31 16G1T1	
7		1. OBD() () 2. AD	

- 3 ≤ 95%
- 4 0.4 0.6Mpa

1 7 ´ Ç Ç л л θ с ĩ Å Ç , ƒ φт Ç î Ğ

2

16G 1T

4.1.1.2 2

4.1.2

0 120000cd ± 12%

—	35cm/dam	52.5cm/dam	2 ° ~	3 °
—	52.5cm/dam	52.5cm/dam	3 °	3 °
—	35cm/dam	52.5cm/dam	2 ° ~	3 °
—	52.5cm/dam	52.5cm/dam	3 °	3 °
—	35cm/dam	52.5cm/dam	2 °	3 °

350 1400mm ± 10mm

CV j 0 -10 50

≤ 90%

70.0kPa 106.0kPa

0.4-0.6MPa

50Hz ± 1Hz

5m

AC 220V ± 10%

4.3

γ,

4.4

4.4.1

4.4.1.1 win11/64

16G 1T

4.4.1.2 2

*4.4.1.3

4.4.1.3.1 ABS/ESC

4.4.1.3.2 7 ABS/ESC

4.4.1.3.3

4.4.1.3.4 ABS/ESC

*4.4.1.4 0.8

2.1

4.4.2

GB7258-2017 GB23890-2020 GB/T13564

mm	*	0.8—2.1	25CM
mm	*	0.8—2.1	25CM
daN		$\geq 1500 \times 2$	
daN		1	
%		$\leq \pm 3$	
/		$\leq \pm 2$	
kW		$7.5\text{kW} \times 2$	
		2.5	
ABS	km/h	0-10	
ABS			

4.4.3



4.4.4

4.4.4.1

14

80

3

96

14

7.5—7.9,

0.8

4.4.4.2

4.4.4.3

4.4.4.4

4.4.4.5

$\dot{\omega}$

44414.6 ABS
ECU

, ABS

4.4.5

0.35 4445 1 ρ

S

*

4.6

4.7.1

win11/64

4.7.2

OBD() (

)

4.7.3

AD

4.7.4

1

***4.7.5**

ECU

ECU

OBD

***5.1**

5%

***5.2**

Ã

***5.3**

Ã

5.4

Ã

5.5

90

È

6.4

6.5



6.6

6.7

2

1)

2)

3)

CAD

4)

5)

6)

U

7)

8)

9)

10

6.8

7.1

*7.2

7.3

7.4 6

12 18 24

7.5 2

24

48

7.6 30

2 2 /

3

7.7

7.8

7.9 /

;